



# G97-2.0 MW

## Technical specifications

# G97-2.0 MW

## General details

Rated power	2.0 MW <sup>(1)</sup>
Wind class	IEC IIA/IIIA/S
Control	Pitch and variable speed
Standard operating temperature	Range from -20°C to 30°C <sup>(2)</sup>

## Rotor

Diameter	97 m
Swept area	7,390 m <sup>2</sup>
Power density	270.6 W/m <sup>2</sup>

## Blades

Length	47.5 m
Airfoils	LM Wind Power proprietary airfoils
Material	Fiberglass reinforced with polyester resin

## Tower

Type	Tubular steel tower
Height	78, 90, 100, 104 <sup>(3)</sup> and 120 m

## Gearbox

Type	1 planetary stage 2 parallel stages
------	--

## Generator

Type	Doubly-fed induction machine
Voltage	690 V AC
Frequency	50 Hz/60 Hz
Protection class	IP 54
Power factor	0.95 CAP-0.95 IND throughout the power range <sup>(4)</sup>

<sup>(1)</sup> 2.1 MW nominal power upgrade available depending on the site.

<sup>(2)</sup> Different versions and optional kits are available to adapt machinery to high or low temperatures and saline or dusty environments.

<sup>(3)</sup> Class S.

<sup>(4)</sup> Power factor at generator output terminals, on low voltage side before transformer input terminals.

Siemens Gamesa Renewable Energy, S.A.  
Parque Tecnológico de Bizkaia, Edif. 222  
48170, Zamudio, Vizcaya, Spain  
Phone: +34 944 03 73 52  
onshoresales@siemensgamesa.com  
www.siemensgamesa.com

09/2018